



Lift It... Move It... Safely!

| Pro Series | Lift Cap (lb) | Proof Load (lb) | Lift Range (in) | Max Assembled Height (in) | Std Beam Length (ft) | Max Beam Length (ft) | Height Adjust (in) | Caster Spread (in) | Assembled Weight (lb) | Moveable Under Load? | Cantilever Capable? | Split Beam Capable? |
|----------------------------|---------------|-----------------|-----------------|---------------------------|----------------------|----------------------|--------------------|--------------------|-----------------------|----------------------|---------------------|---------------------|
| 1100R | 1,100 | 1,650 | 66-90 | 105 | 8 | 30.0 | 6 | 48 | 250 | ✓ | ✓ | ✓ |
| 2200R | 2,200 | 3,300 | 66-90 | 105 | 8 | 26.0 | 6 | 48 | 270 | ✓ | ✓ | ✓ |
| 2200LW | 2,200 | 3,300 | 82-122 | 138 | 10 | 26.0 | 8 | 65 | 300 | ✓ | ✓ | ✓ |
| 4400M | 4,400 | 6,600 | 66-90 | 105 | 10 | 15.0 | 6 | 48 | 290 | ✓ | ✓ | ✓ |
| 4400R | 4,400 | 6,600 | 82-122 | 138 | 10 | 15.0 | 8 | 65 | 350 | ✓ | ✓ | ✓ |
| 4400T | 4,400 | 6,600 | 98-138 | 153 | 15 | 15.0 | 8 | 67 | 380 | ✓ | ✓ | ✓ |
| 6600R | 6,600 | 9,900 | 106-154 | 178 | 15 | 16.5 | 8 | 73 | 585 | ✓ | ✓ | ✓ |
| 11000R | 11,000 | 16,500 | 106-154 | 178 | 15 | 16.5 | 8 | 73 | 715 | ✓ | ✓ | ✓ |
| 16500R | 16,500 | 20,625 | 97-139 | 173 | 15 | 15.0 | 7 | 81 | 955 | ✓ | ✓ | |
| 22000R | 22,000 | 27,500 | 97-139 | 169 | 15 | 15.0 | 7 | 81 | 975 | ✓ | ✓ | |
| Can Feature be Customized? | ✓ | | ✓ | ✓ | | ✓ | ✓ | | | | ✓ | ✓ |

Beam Clear Span: 3 ft. less than Beam length **Distance Between Casters:** 1 foot less than Beam length
 Custom 2200XT and 4400XT Models Available. Contact **eme** for specs and pricing.

Documentation Supplied with each **eme** Gantry and Davit Crane

1. Engineer's Stamped Drawing
2. Signed Certificate of Test (crane tested to Proof Load)
3. Operator's Manual
4. 10 Year Warranty against Manufacturer's Defects

All welding on Gantry and Davit Cranes, Sockets performed by certified shop
 Struts and Leg Extrusions matched to Gantry Capacity and Lift Height
 Locking 'Surround-Beam' Trolley is Standard with all **eme** Gantry Cranes
 All Gantry Cranes Proof Tested to 125 to 150% of Rated Capacity before shipment to customer
 Locking Casters (independently for swivel, roll) Gantry can be rolled when loaded
 Gr. L9 Chromate Plated Fasteners. Bolted Assembly is the stronger assembly than with pins
 North American made; North American parts; built for North American conditions
 All Gantry Cranes can be assembled from the Ground Up with 1-4 people
 Two wrenches only tools needed to assemble any **eme** Gantry Crane
 Extruded engineered hollow Box-Beams stronger and lighter than steel 'I' beams

Contact **eme** at **888-679-5283** for current information, pricing, parts
 For Parts: parts@easilymovedequipment.com