



## Lift It... Move It... Safely!

Pro Series	Lift Cap (lb)	Proof Load (lb)	Lift Range (in)	Max Assembled Height (in)	Std Beam Length (ft)	Max Beam Length (ft)	Height Adjust (in)	Caster Spread (in)	Assembled Gantry Weight (lb) <sup>(a)</sup>	Moveable Under Load?	Cantilever Capable?	Split Beam Capable?
1100R	1,100	1,650	66-90	105	8	30.0	6	48	235	✓	✓	✓
2200R	2,200	3,300	66-90	105	8	26.0	6	48	255	✓	✓	✓
2200LW	2,200	3,300	82-122	138	10	26.0	8	65	285	✓	✓	✓
4400M	4,400	6,600	66-90	105	10	15.0	6	48	275	✓	✓	✓
4400R	4,400	6,600	82-122	138	10	15.0	8	65	335	✓	✓	✓
4400T	4,400	6,600	98-138	153	15	15.0	8	67	365	✓	✓	✓
4400XT	4,400	6,600	120-176	191	15	15.0	8	84	400	✓	✓	✓
6600R	6,600	9,900	106-154	178	15	16.5	8	73	550	✓	✓	
11000R	11,000	16,500	106-154	178	15	16.5	8	73	680	✓	✓	
16500R	16,500	20,625	100-142	173	15	15.0	7	81	900	✓	✓	
22000R	22,000	27,500	97-139	169	15	15.0	7	81	905	✓	✓	
Can Feature be Customized?	✓		✓	✓		✓	✓				✓	✓

(a) Excludes the weight of the beam trolley. Beam trolley weights are as follows: 4400 series, 15lbs; 6600R/11000R, 35lbs; 16500R, 55lbs; 22000R, 70lbs

### Documentation Supplied with each **eme** Gantry and Davit Crane

1. Engineer's Stamped Drawing
2. Signed Certificate of Test (crane tested to Proof Load)
3. Operator's Manual
4. 10 Year Warranty against Manufacturer's Defects

All welding on Gantry and Davit Cranes, Sockets performed by certified shop  
 Struts and Leg Extrusions matched to Gantry Capacity and Lift Height  
 Locking 'Surround-Beam' Trolley is Standard with all **eme** Gantry Cranes  
 All Gantry Cranes Proof Tested to 125 to 150% of Rated Capacity before shipment to customer  
 Locking Casters (independently for swivel, roll) Gantry can be rolled when loaded  
 Gr. L9 Chromate Plated Fasteners. Bolted Assembly is the stronger assembly than with pins  
 North American made; North American parts; built for North American conditions  
 All Gantry Cranes can be assembled from the Ground Up with 1-4 people  
 Two wrenches only tools needed to assemble any **eme** Gantry Crane  
 Extruded engineered hollow Box-Beams stronger and lighter than steel 'I' beams

Contact eme at **888-679-5283** for current information, pricing, parts

For Parts: [parts@easilymovedequipment.com](mailto:parts@easilymovedequipment.com)

[www.easilymovedequipment.com](http://www.easilymovedequipment.com)